

Finishing Tools

Spiked Rollers

MADE IN THE USA

We are one of the very few manufacturers in the world to offer rigid solvent-resistant and aluminum cored polypropylene spiked rollers for the floor coating industry.

These spiked rollers are vital in ensuring proper floor coating material adhesion. They are designed to be used on freshly applied floor coatings for the purpose of releasing trapped gas as well as to assist in the leveling process of several varieties of floor coatings. These rollers are easy to clean, allowing for repeated use. The applicator should also wear spiked shoes while using a spiked roller (see page 6).

We manufacture our spikes and end caps out of solvent-resistant High-Density (HD) and Ultra-High Molecular Weight (UHMW) Polyethylene, respectively, for easier cleanup and extended wear. We're sure you will find these tools worth cleaning! Spikes are available in 7/16", 9/16" and 13/16" lengths. Our most popular widths are 9", 18" and 24". Our rollers also come in 36" and 48" widths, which are preferred by some applicators when very large, flat areas need to be treated quickly. We also have 1-1/2" and 3" widths on special frames for very tight areas. All of our rollers, 9" or wider, come with a heavy-duty aluminum frame and high-grade stainless steel axles and our superior gusset bracing with a maximum strength threaded handle adapter. Our 9" rollers also come on a special radial frame with a threaded handle adapter. (See 59009 below). The 1-1/2" and 3" rollers come on special handled frames. (Standard cage style paint-roller frames do not work with our 9" Spiked Rollers). Replacement rollers for all width and spike lengths are available as are replacement frame assemblies (see page 14).

- 1-1/2" with 7/16" spikes - 59001
- 3" with 7/16" spikes - 59003
- 3" with 9/16" spikes - 59403
- 3" with 13/16" spikes - 59103



For Handle Options



9/16" Super Sharp (44 Spikes)

Heavy-Duty Aluminum Frame

Head Width	Radial Roller Frame	Threaded Handle Adapter	66" Handle	Replacement Roller
9"	59458	59459	59559	SA10062
18"	-	59468	59568	SA10063
24"	-	59474	59574	SA10064
36"	-	59486	59586	SA10065
48"	-	59498	59598	SA10066

7/16" Super Sharp (33 Spikes)

Heavy-Duty Aluminum Frame

Head Width	Radial Roller Frame	Threaded Handle Adapter	66" Handle	Replacement Roller
9"	59009	59209	59509	SA10043
18"	-	59218	59518	SA10023
24"	-	59224	59524	SA10025
36"	-	59236	59536	SA10026
48"	-	59248	59548	SA10027

13/16" Super Sharp (33 Spikes)

Heavy-Duty Aluminum Frame

Head Width	Radial Roller Frame	Threaded Handle Adapter	66" Handle	Replacement Roller
9"	59109	59309	59609	SA10044
18"	-	59318	59618	SA10029
24"	-	59324	59624	SA10030
36"	-	59336	59636	SA10031
48"	-	59348	59648	SA10032

Helpful Hints...

Many factors can contribute to the creation of trapped gas bubbles in freshly applied protective coatings, particularly on floors. Our 7/16" and 13/16" Super Sharp Spiked Rollers are effectively used on most floor coatings and your choice between the two depends on the mil thickness specifications of the material being applied.

Where a great abundance of bubbles are anticipated or seen, our 9/16" Super Sharp Spiked Rollers are ideal because of the greater number of spikes per square inch of roller surface.

Most often, either the 7/16" or the 13/16" Super Sharp Spiked Rollers are adequate to get the job done.